

類比與脈波輸入流量瞬間量/累積量/批量顯示控制電錶 (PULSE/ANALOG INPUT FLOW RATE/TOTALIZER/BATCH CONTROLLER (two-stage)METER)

**MODEL
MRT-B**



■特點(FEATURES)

- 精確度0.05%滿刻度±1位數(Accuracy 0.05% F.S.±1digit)
- 可同時量測與顯示瞬間量(5位數)/批量(6位數)/累積量(10位數)
(Measuring and display rate(5 digits)/batch(6 digits)/totalizer(10 digits))
- 5種流量單位可任意設定(Display flow unit TON/M³/Liter/GAL/CC can be modified)
- 4種時間基數可任意規劃(1或60或3600或86400秒)
(Programable time base(1 or 60 or 3600 or 86400 second))
- 批量控制採用前置量預停設定方式(Prestop counting function)
- 批量控制具有向上或向下計數模式可規劃(Two-counting mode Up/Down for batch controller)
- 面板具有起動/停止/批量復歸按鈕功能
(Front panel push buttons allow the operator to start/stop/batch reset function)
- 具有累積量同步脈波輸出功能(Synchronize totalizer of pulse output function)
- 防護等級NEMA4/IP64(Protection class NEMA4/IP64)

1.MODEL:MRT-B -

(選購型號)

NO	Input Type	NO	Input Type	NO	Linearity function	NO	Alarm output	NO	Analog output	NO	RS-485	NO	Aux. Power
A	DC1~5V & NPN/PNP Voltage pulse	O	SPECIFIED	N	None	0	None	N	None	N	None	A	AC/DC18~60V
B	DC4~20mA & NPN/PNP Voltage Pulse	Y	16 point(linearity) (input impedance=50 ohm)	Y	16 point(linearity) (input impedance=50 Kohm)	2	Rate/Totalizer	I	DC4~20mA	Y	RS-485	B	AC/DC90~260V
C	DC1~5V & Magnetic pick-up				• Only analog input type		• Relay contact(AC250V-5A DC30V-7A)	V	DC0~10V		• Modbus RTU mode • 256 nodes on bus		• Less 5VA for AC/DC input
D	DC4~20mA & Magnetic pick-up							R	SPECIFIED				

2.SPECIFICATION (主要規格)

- Measuring accuracy (精確度) : 0.05% F.S.±1 digit(Rate/Analog input) (23±5°C)
- Readout/compare range (顯示值/比較值範圍) : 0~99999 digit(Rate)/0~999999 digit(Batch) 0~9999999999 digit(Totalizer)
- Input type (輸入型式) : In side jump selectable:
DC4~20mA/DC1~5V(Analog)
Current sourcing(NPN)/Current sinking(PNP)/
Switch contact(Pulse)
- Count input trigger levels (脈波觸發電位) : High level: V_{IH}=DC4~30V(Pulse)
V_{IH}=AC30mV~30V(Magnetic pick-up)
V_{IH}=Rmax.<500 ohm(Switch contact)
Low level: V_{IL}=DC0~2V(Pulse)
V_{IL}=AC0~20mV(Magnetic pick-up)
V_{IL}=Rmax.>1K ohm(Switch contact)
- Max.count rates (最高輸入頻率) : <10KHz(50% duty cycle(Pulse))
<1KHz(Magnetic pick-up)
<100Hz(Switch contact)
- Batch controller start time delay (批量控制輸出2起動延遲時間) : 0 to 99 second adjustable(Output2)
- Batch controller prestop range (批量控制輸出2預停前置量) : 0 to 9999 digit adjustable(Output2)
- Batch controller counting modes (批量控制輸出復歸方式) : Up or Down can be modified
- Batch controller output reset type (批量控制輸出復歸方式) : Manual(N) or Auto restart(A) can be modified
- Analog output resolution (類比輸出解析度) : 16 bit DAC
- Response time (輸出反應速度) : < 50ms(0~90%)
- Output drive capability (輸出負載能力) : < 10mA for voltage mode
< 10V for current mode
- Pulse output (脈波輸出容量) : Photo couple of open-collector(Max.DC30V/50mA)
(Synchronize totalizer)(Max.100Hz)
- RS-485 address (通訊位址) : "01"~"FF"(0~255)
- RS-485 baud rate (傳輸速度) : 38400/19200/9600/4800/2400 selective
- Temp. coefficient (溫度係數) : 50ppm/°C (0~50°C)
- Display (Rate/Totalizer) (顯示幕) (Batch) : Red high efficiency LEDs high 10.16mm(0.4")
Red high efficiency LEDs high 7.0mm(0.28")
- Memory mode (記憶型式) : Non-volatile E² PROM memory
- Dielectric strength (絕緣耐壓能力) : 2KVac/1 min. (input/output/power)
1600Vdc (input/output)
- Operating condition (使用環境條件) : 0~50°C (20 to 90% RH non-condensed)
- Storage condition (存放環境條件) : 0~70°C (20 to 90% RH non-condensed)
- CE EMC Certification (CE認證) : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

